

## Universal Bevel Protractor 106 UF



### Features



- With fine adjustment
- Stainless steel
- Vernier scale and main scale both have a satin chrome finish to prevent glare and to enable parallax free reading on the same plane
- Knurled screw for clamping the interchangeable beam into position
- Scope of supply: Magnifying reading lens, interchangeable beam and case

### Technical Data

Blade length mm (inch)	Range degrees	Readings minutes	Deviation minutes	Order no.
150 (6")	360°	5'	5'	4214050
200 (8")	360°	5'	5'	4214051
300 (12")	360°	5'	5'	4214052

### Accessories

	Order no.
<b>Interchangeable Beams</b> Stainless steel, hardened (standard accessories) beam length	<b>106 Us</b>  150 mm / 6" 4214010 200 mm / 8" 4214011 300 mm / 12" 4214012
<b>Additional Accessories</b>	
<b>Stand</b> Featuring flat and V-surface for dia. 5 – 30 mm length 90 mm, width 25 mm	<b>106 UFv</b>  4214061
<b>Acute Angle Attachment</b> for particularly small acute angles. Screws onto the beam	<b>106 UFw</b>  4214062



## Digital Universal Bevel Protractor 106 ES



### Features

- Easy to read high contrast 8,5 mm high LCD
- Displays the angular degrees and angular minutes or decimal degrees
- Zero setting at any position of the measuring range
- Beam can be clamped with a push button
- Fine adjustment for easy setting of a desired angle
- Locking lever to prevent accidental adjustment
- Base plate and beam are made of stainless steel, the measuring edges hardened
- Data output: Opto RS232C
- Max. setting speed 3 rotations per second
- Capacitive measuring system, life of the battery approx. 2 years
- Scope of supply: Battery, 300 mm beam and case

### Technical Data

Range	Resolution	Deviation switchable	Order no.
1 x 360° or	1 minutes or 0,01° 2 x 180° or 4 x 90°	± 2 minutes	4214600

### Accessories

	Order no.
<b>Interchangeable Beams</b>	<b>106 ESs</b>
Stainless steel, hardened beam length	
150 mm / 6"	4214620
200 mm / 8"	4214621
300 mm / 12"	4214622
<b>Battery 3V, Type CR 2032</b>	<b>4102520</b>
<b>Data Connection Cable Opto RS232C (2 m), with SUB-D Jack 9 pin</b>	<b>16 ESv</b>
	<b>4102510</b>
<b>Stand</b>	<b>106 ESv</b>
Featuring flat and V-surface for dia. 5 – 30 mm, length 90 mm, width 25 mm	
	<b>4214630</b>
<b>Acute Angle Attachment</b>	<b>106 UFw</b>
for particularly small acute angles. Screws onto the beam	
	<b>4214062</b>

